

**2MP 4 IN 1 Ultra Low Light Dome Camera**



**Functions:**

- Up to 2 megapixel resolution
- Ultra low illumination
- Lens (3.6) mm
- Support AHD,TVI,CVI
- Approx. 25 meters IR range
- True Day/Night, 3D DNR,
- Wide Dynamic Rang (90 dB)
- IP67 / Vandal Proof
- UTC Support
- 12V DC±10%

<b>Model</b>	<b>MNA-ADC2DWD-IF</b>
	<b>2MP 4 in 1 Ultra Low Light Camera</b>
<b>Camera</b>	
Image Sensor	1/2.9" SONY Starvis CMOS Sensor
Min. Illumination	Color : 0.005 lux (F1.2,AGC ON) B/W : 0.0005 lux (F1.2,AGC ON)
Day & Night	ICR
Focus Mode	Fixed
Shutter Time	50Hz: 1/1-1/100,000s; 60Hz: 1/1-1/100,000s
S / N Ratio	>52dB
Audio Compression	-
White Balance	Auto / Manual /ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp
AGC	Auto / Manual
<b>Lens</b>	
Focal Length	(3.6) mm
Iris	Fixed
<b>Image</b>	
Video Output Mode	AHD/TVI/CVI: 2M@30fps/25fps
Back Light	BLC, WDR (90 db)
Infrared Distance	Approx. 25 meters
Others	Privacy Mask, 3D DNR,UTC ,Dfog
<b>General</b>	
Power	12 V DC ± 10%
Working Temperature / Humidity	-30 - +65, 97%
Protection Level	IP67 - IK10
Power Consumption	Max. 900 MA
Dimensions(mm)	94(W) x 94(H) x 72(D)mm
Standard	EN ,RCII Iran standard
Weight (approx.)	0.4 kg