

2MP 4 IN 1 Ultra Low Light Bullet Camera



Functions:

- Up to 2 megapixel resolution
- Ultra low illumination
- Motorized Zoom Lens (2.8-13.5) mm
- Smart Focus
- Support AHD,TVI,CVI
- Approx. 30 meters IR range
- True Day/Night, 3D DNR,
- Wide Dynamic Rang (120 dB)
- IP67 / Vandal Proof
- UTC Support
- 12V DC±10%

Model	MNA-ADC2TWD-IFVZ
	2MP 4 in 1 Ultra Low Light Dome Camera
Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Min. Illumination	Color : 0.002 lux (F1.2,AGC ON) B/W : 0.0002 lux (F1.2,AGC ON)
Day & Night	ICR
Focus Mode	Smart Auto
Shutter Time	50Hz: 1/1-1/100,000s; 60Hz: 1/1-1/100,000s
S / N Ratio	>52dB
Audio Compression	-
White Balance	Auto / Manual /ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp
AGC	Auto / Manual
Lens	
Focal Length	(2.8-13.5) mm / Motorized
Iris	Auto / Manual
Image	
Video Output Mode	AHD/TVI/CVI: 2M@30fps/25fps
Back Light	BLC, WDR (120 db)
Infrared Distance	Approx. 30 meters
Others	Privacy Mask, 3D DNR,UTC,Dfog
General	
Power	12 V DC ± 10%
Working Temperature / Humidity	-30 - +65, 97%
Protection Level	IP67 - IK10
Power Consumption	Max. 900 MA
Dimensions(mm)	φ142 x 142(H) mm
Standard	EN ,RCII Iran standard
Weight (approx.)	1 kg