

## 32 Channel Professional 4K NVR



### Functions

- Linux Base.
- Support liveview, storage, and playback of the connected camera with up to the resolution of 12 megapixels.
- Connectable to the third-party network
- Raid Support
- 4 SATA hard disks up to 40TB
- Support HDD Quota and Group Modes
- Self-adaptive 2\*10M/100M/1000M network interfaces, with working modes configurable: multi-address, load balance, network fault tolerance, etc.
- Bandwith Management
- Support HDD Quota and Groups Mode
- Support Advance Video Analytics (VCA )
- Simultaneous HDMI, VGA outputs and respective live view and playback via VGA and HDMI outputs.
- Up to 16-ch synchronous playback.
- Smart search for the selected area in the video
- ANR technology to enhance the storage reliability when the network is disconnected
- Triple Stream Support
- Alarm Managmnet
- Face Reception : Support up to 15,000 Face (Option)

<b>Model</b>	<b>MNA-NVR432-4KR</b>
	<b>32 Channel Professional 4K NVR</b>

### Video/Audio input

IP video input	32 Channel
Two-way audio	Support

### Video/Audio output

HDMI output	HDMI *2 : up to 4K
VGA output	VGA *1 : up to 2K
Audio output	1 Channel Duplex

### System

Os	Dual OS design Linux Base
internal Web Server	Support
Support Resolution	12MP/8MP/6MP/5MP /3MP /1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF
Bandwidth	Incoming 320 Mbps /Outgoing 320 Mbps
Decoding Format	H264/H264+/H265/H265+/MJPEG

Video Analytics	Advance VCA Support : Linecrossing , intrusion detection, Region Entrance, Region Exiting, Unattended Baggage, Object Removal, Defocus Detection, Audio High/Low Detection, Objects Counting, Face Detection, Scene Change
-----------------	---

Synchronous playback	UP to 4K
----------------------	----------

Audio Decoding Format	G722.1/G.711ulaw/G.711alaw/MP2L2/G.726
-----------------------	--

### Hard disk

SATA	4 SATA interfaces for 4 HDDs
------	------------------------------

Capacity	Up to 10TB capacity for each HDD
----------	----------------------------------

### Disk array

Groups	Support HDD Quota and Groups Mode
--------	-----------------------------------

Number of array	0,1,5
-----------------	-------

### External interface

Network interface	2 * RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interfaces
-------------------	--

Serial interface	RS-232; RS-485; Keyboard
------------------	--------------------------

USB interface	2 × USB 2.0, 1XUSB 3.0
---------------	------------------------

Alarm in/out	16/4
--------------	------

### Others

Power supply	100 ~ 240 VAC, 6.3 A, 50 ~ 60 Hz
--------------	----------------------------------

Certificate	ONVIF, PSIA, RCII of Iran standard
-------------	------------------------------------

Working temperature	-10 °C ~ +55 °C
---------------------	-----------------

MTBF	MTBF >120,000 hrs Confirmed by Windchill Quality Solutions
------	--

Chassis	1 U chassis
---------	-------------

Dimensions (W × D × H)	440mm × 344mm × 50mm
------------------------	----------------------

Weight	≤ 5.5 Kg ( without hard disks )
--------	---------------------------------

Max Power	12V DC Power Consumption: ≤ 12W (without HDD)
-----------	--