

4MP Network Mini Dome Camera



Functions

- Up to 4 megapixel resolution
- low illumination
- Fixed Lens (2.8)mm
- Approx. 30 meters IR Range
- True Day/Night , 3D DNR
- Wide Dynamic Rang
- Low Bit Rate / ROI /H265 Plus
- IP67 / Vandal Proof IK10
- 3-axis Adjustment
- Onvif , CGI , PSIA Support
- 12V DC±10% & PoE(802.3af Class3)

Model	MNA-DC4DWD-IF
	4MP Network Mini Dome Camera

Camera

Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	Color : 0.03 lux (F1.2,AGC ON) B/W : 0.001 lux (F1.2,AGC ON)
Day & Night	ICR
Focus Mode	Fixed
Shutter Time	50Hz: 1/1-1/1,000,000s; 60Hz: 1/1-1/1,000,000s
S / N Ratio	>52dB
Audio Compression	-
White Balance	Auto / Manual /ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp
AGC	Auto / Manual

Lens

Focal Length	2.8 mm @ F1.4,
Angle of View	Angle of view:112 (Wide)
Iris	Fixed

Image

Main & Sub Stream	4MP (2592*1520) 20fps; 1080P, 720P
Third Stream	(720*576), Max 20fps
Back Light	BLC, WDR (100db)
Image Compression	H265/H.264 Plus / H264 / MJPEG
Audio Compression	-
SVC	-
ROI	Support 2 areas with adjustable levels
Protocols	IPv4/IPv6,HTTP,HTTPS,802.1x,Qos,FTP,SMTp,UPnP,SNMP, DNS,DDNS,NTP,RTSP,RTP,TCP,UDP,IGMP,ICMP,DHCP,PPPoE
Standard	ONVIF, PSIA, CGI
Others	Privacy Mask, 3D DNR,HLC,Dfog

Pan & Tilt

Angle Of Adjustment	3-axis Adjustment , Pan:-30° - +30°, Tilt: 0° - 75°, Rotation: 0° - 360°
---------------------	--

System Integration

IR Range	Approx. 30 meters
Alarm I/O	-
Alarm Dtection	Motion detection, Tampering alarm, Network disconnect, IP address confict, ,Intrusion detection
Audio I/O	-
Ethernet	10Base-T / 100Base-TX, RJ45 connector
Onboard Storage	-
Number of Simultaneous Live View	Up to 30
Network Storage	NAS/ANR
User/Host Level	Up to 32 users,3 Levels: Administrator, Operator and User

General

Power	12 V DC ± 10% , PoE (802.3af)
Working Temperature / Humidity	(-30 - +60) 90% or less
Protection Level	IP67 – Vandal Proof IK10
Power Consumption	Max. 4.5 W
Dimensions(mm)	Φ108.5 x 81mm
Standard	EN ,RCII Iran standard
Weight (approx.)	450gr