

8MP 38X Network Ultra low light IR Speed Dome



Functions

- (3840*2160) 4K Resolution
- Ultra low illumination
- Wide movement range
- 38X optical zoom, 16X digital zoom
- High Power IR Up to 250M
- True Day/Night, WDR, 3D DNR
- Optical Dfог
- Optical EIS - (gyroscope)
- 3D intelligent positioning
- Audio/Alarm I/O
- Video Analytics
- Low Bit Rate / ROI
- IP66
- Onvif , CGI , PSIA Support
- Built-in Memory slot, up to 256 GB
- Internal Surge protection

Model	MNA-SP8DF-38IR250
	8MP 38X Network ultra low light IR Speed Dome
Camera	
Image Sensor	1/1.8" HD CMOS sensor
Min. Illumination	Color : 0.003 lux (F1.6, 1/1 sec, 50 IRE, AGC On) B/W : 0.0005 lux (F1.6, 1/1 sec, 50 IRE, AGC On)
Day & Night	ICR
Focus Mode	Auto / Semiautomatic / Manual
Shutter Time	50Hz: 1/1-1/30,000s; 60Hz: 1/1-1/30,000s
S / N Ratio	>52dB
Digital Zoom	16X
White Balance	Auto / Manual /ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp
AGC	Auto / Manual
Lens	
Focal Length	5.7~216 mm, 38x
Angle of View	60.6° ~ 1.6° degree (Wide-Tele)
Min. Working Distance	10-1500mm(Wide-Tele)
Image	
Main Stream	8MP (3840*2160), Max 30fps
Sub Stream	2MP (1920*1080), Max 30fps
Third Stream:	D1 (720*576), Max 30fps
WDR	120db
Image Compression	H265 Plus/H.264(Baseline, Main, High Profile)/MJPEG/MPEG4
Audio Compression	G722.1/G.711ulaw/G.711alaw/MP2L2/G.726
SVC	Support
ROI	Support 8 areas with adjustable levels
Protocols	IPv4/IPv6,HTTP,HTTPS,802.1x,Qos,FTP,SMTP,UPnP,SNMP, DNS,DDNS,NTP,RTSP,RTP,TCP,UDP,IGMP,ICMP,DHCP,PPPoE
Standard	ONVIF, PSIA, CGI
Others	Optical Defog, Optical EIS, Privacy Mask, 3D DNR, BLC, HLC
Pan & Tilt	
Movement Range	Pan: 360° endless, -5°-90°(Auto Flip)
Movement Speed	Pan Preset Speed: 500°/s / Tilt Preset Speed: 400°/s
Number of Preset	300
Patol	8 patrols, up to 32 presets per patrol
Pattern	4 patterns, with the recording time not less than 10 minutes per pattern
Power-off Memory	Support
Park	Support
Proportional Zoom	Support
PTZ Position Display	On / Off
System Integration	
3D Positioning	Support
Preset Freezing	Support
Scheduled Task	Support
Alarm I/O	7 alarm inputs, 2 alarm outputs, alarm linkage
Alarm Dtection	Smart-tracking ,Intrudsdn detection, Line crossing detection, Motion detection, Audio Exception Detection, Dynamic analysis, Tampering alarm, Network disconnect, IP address conflict, Storage exception
Audio I/O	1/1
Ethernet	10Base-T / 100Base-TX, RJ45 connector
CVBS Output	1.0V[p-p] / 75Ω, NTSC (or PAL) composite, BNC
RS485	Half duplex, Pelco-P, Pelco-D, self-adaptive
Onboard Storage	Built-in Micro SD/SDXC card slot, up to 256 GB edge recording
IR	Up to 250M, Adjustable by zoom
User/Host Level	Up to 32 users,3 Levels: Administrator, Operator and User
Wiper	-
General	
Power	AC24V, HI-POE+ Max. 56W
Working Temperature / Humidity	-40 - + 70 - 90% or less
Protection Level	IP66 TVS 6,000V lightning protection, surge protection and voltage transient protection Fan - Heater
Dimensions(mm)	Φ266.6(mm)×365.2(mm)
Weight (approx.)	10 kg