

2MP Network Ultra Low Light Dome Camera



Functions:

- Up to 2 megapixel resolution
- Ultra low illumination
- 2.8 ~ 13.5mm, motorized zoom lens
- Approx. 40 meters Smart IR
- True Day/Night , 3D DNR,Dfog
- Wide Dynamic Rang (120 dB)
- Deep learning Video Analytics (Reduce)
- False Alarm)
- Smart Face detection Capture
- Low Bit Rate / ROI /H265 Plus
- IP67 / Vandal Proof -IK10
- Built in Microphone
- 3-axis Adjustment
- Onvif , CGI , PSIA Support
- Built-in Memory slot, up to 256GB
- 12V DC±10% & PoE(802.3af Class3)

MNA-DC2TWDLL-IFVSZM

2MP Network Ultra Low Light Dome Camera

Camera

Image Sensor	1/2.8" Progressive Scan CMOS
Day & Night	ICR, schedule
Min. Illumination	Color : 0.0005 lux (F1.2,AGC ON) B/W : 0.00001 lux (F1.2,AGC ON)
Shutter Time	50Hz: 1/1-1/100,000s; 60Hz: 1/1-1/100,000s
S / N Ratio	>56dB
Audio Compression	G.711
White Balance	Auto / Manual /ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp
AGC	Auto / Manual

Lens

Focal Length	2.8 ~ 13.5mm, AF Smart focusing and motorized zoom lens
Angle of View	127.4° ~ 36.2°
Focus Mode	Auto

Image & Audio

Main & Sub Stream	2MP (1920*1080), Max 30fps; 720P (1280*720), Max 30fps;
Third Stream	D1 (720*576), Max 30fps; 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;
Back Light	BLC, WDR (120 db)
Image Compression	H.265 Plus/H265 / H264 /MJPEG
Audio Compression	G.711ulaw/G.711alaw
SVC	Support
ROI	Support 8 areas with adjustable levels
Protocols	IPv4/IPv6,HTTP,HTTPS(SSL) ,802.1x,Qos,FTP,SMTP,UPnP,SNMP, DNS,DDNS,NTP,RTSP,RTP,TCP,UDP,IGMP,ICMP,DHCP,PPPoE
Standard	ONVIF (S,G,T), PSIA, CGI
Others	HLC,Dfog, Privacy Mask, 2D/3D DNR, Corridor Mode

System Integration

IR Range	Smart - Approx. 40 meters – Control by On/Off
Alarm I/O	1/1

General Function:

Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication, Advance Motion detection up to 4 separated area

Video analytics (Deep Learning Technology) :

Linecrossing ,intrusion detection(Focus on human, vehicle and non-motor vehicle),Region Entrance,Region Exiting, Object Left/Removal, Audio High/Low Detection ,Crowd Detection,People counting
Deep learning Face Detection(Face capture) Capture up to 40 faces in the same picture

Audio I/O	1/1 – Two Way Built-in Mic
Ethernet	10Base-T / 100Base-TX, RJ45 connector
Onboard Storage	Built-in Micro SD/SDXC card slot, up to 256 GB edge recording
Network Storage	NAS/ANR
Number of Simultaneous Live View	Up to 30
User/Host Level	Up to 32 users,3 Levels: Administrator, Operator and User

General

Power	12 V DC ± 10% , PoE (802.3af)
MTBF	MTBF >120,000 hrs Confirmed by Windchill Quality Solutions
Working Temperature / Humidity	-35 - +65, 90% or less
Protection Level	IP67 – IK10 - Surge Protection 6KV
Power Consumption	Max. 9W
Dimensions(mm)	Φ148 x 111.3mm
Standard	EN ,RCII Iran standard
Weight (approx.)	0.75 kg