

Enterprise 32 Channel 4K NVR



Functions

- Dual-OS design Linux to ensure the security of system running.
- Intel DSP Chipset
- Support liveview, storage, and playback of the connected camera with up to the resolution of 12 megapixels.
- Connectable to the third-party network cameras Onvif Profile S & G & T
- Failover & Hotspare included
- 8 SATA hard disks and 1eSATA disks can be connected for External recording and backup
- Support RAID 0,1,5,6,10 storage scheme. And 8 arrays can be configured
- Either Normal or Fail Over working mode is configurable to constitute a Redundent system
- Self-adaptive 2*10M/100M/1000M network interfaces
- Simultaneous HDMI, VGA outputs, and respective live view and playback via VGA and HDMI outputs.
- Support virtual matrix video
- ANR Support
- ROI Support
- Up to 16-ch synchronous playback.
- Smart search:
Date,Time,VCA,Alarm,Pre&Post
Frame,Area, Water mark ...
- Video Analytics (AI- Deep Learning Support) Support
- User Permission up to unlimited Level
- Support Face Recognition up to 15000 Face (option)

Model		MNA-NVR832EN-4KR
Enterprise 32 Channel 4K NVR		
Video/Audio input		
IP video input	32 Channel	
Two-way audio	Support	
Video/Audio output		
HDMI output	2 *(HDMI 1 : 4K - HDMI 2: Full HD)	
VGA output	2 *(VGA 1 :2K)	
Audio output	2 Channel-Duplex	
System		
Os	Linux	
Fram Rate	Up to 960fps	
Support Resolution	12MP/8MP/6MP/5MP /3MP /1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF	
Bandwidth	Intel DSP Chipset	384 Mbps Incoming/384 Mbps Outgoing (Total 768 Mbps)
Bandwidth Management	Support (VBR & CBR)	
Decoding Format	H265+/H265/H264/H264+ /MJPG	
Fail Over	Support Intrusion Detection,CrossLine, EnterArea,Leave Area, Defocus Detection, Scene Change Detection, Auto Tracking, Object Left Behind, Object Removed, Vehicle Control, Temperature Detection(Fire Detection,Smoking Detection, Smoke and Fire Detection), Ultra Motion , Traffic Monitoring Motor Vehicle Search, Non-Motor Vehicle Search, Human Body Search, General Search, People Counting Report , People Counting People Flow Counting, Crowd Density Monitoring,	
Video Analytics on edge		
Synchronous playback	16 Channel UP to 4K	
Farsi Calender	Support	
Face Recegnition	Support- up to 15,000 face (option)	
Hard disk		
SATA	8 SATA interfaces for 8 HDDs Up to 15TB capacity for each HDD	
eSATA – External Storage	1 eSATA interfaces	
Disk array		
Array type	RAID 0,1,5,6,10,50 HDD Quota and Group Modes	
ANR & ROI	Support	
External interface		
Network interface	2 * RJ-45 10 /100 /1000 Mbps selfAdaptive Ethernet interfaces	
Serial interface	RS-232; RS-485; Keyboard	
USB interface	5 × USB 2.0 & 3.0	
Integration	Alarm,Access Control,POS,Free SDK	
Alarm in/out	16/4	
Others		
Power supply	100 ~ 240 VAC, 6.3 A, 50 ~ 60 Hz	
Certificate	ONVIF,PSIA,RC1I of Iran standard	
Working temperature	-10 ℃ ~ +55 ℃	
MTBF	MTBF >120,000 hrs Confirmed by Windchill Quality Solutions	
Dimensions (W × D × H)	445 × 496 ×146 mm 19-inch rack-mounted2U chassis	
Weight	≤ 10 Kg (without hard disks)	
Max Power	30 watt (with out HDD)	