


16 Port POE Switch



Functions

- 16 POE Port 10/100 Mbps
- 2 Port Uplink Gb
- POE Support up to 100M
- 200 watt Power Supply
- 11Gb Bandwidth
- Rackmount

MODEL MNA-SW162GN-P

Interfaces

Total Port 24 Ports	Total Port 18 Ports (16 POE + 2 Uplink)
Max POE Output	Max POE Output 200Watt
POE Port Control Texas Instruments Chipset	
RJ45 POE Port	16 Port
Gigabit RJ45 Uplink Port	2
Gigabit SFP Port	-

Network Performance

Standard	IEEE802.3x, IEEE802.3u, IEEE802.3az, IEEE802.3ab, IEEE802.3af, IEEE802.3at
Protocols	CSMA/CD, SSH, SSL, PVE, Storm control, ACLs
Speed & Cabling	Ethernet 10Mbps (half duplex), 20Mbps (full duplex); 10BASE-T: 14,880bps/port Fast Ethernet 100Mbps (half duplex), 200Mbps (full duplex); 100BASE-TX: 14,880bps/port Gigabit Ethernet 1000Mbps (half duplex), 2000Mbps (full duplex); 1000BASE-TX: 1488000bps/port Cabling 10Base-TX: Cat 3 or above Cat.5 UTP(100m) POE=150M 100Base-TX: Cat 5 UTP(100m) POE=100M 1000Base-TX: Cat 6e UTP or Cat 6 UTP(120m) POE=100

Bandwidth	11Gb Internal Bandwidth
MAC Table	64Kb
Auto MDI-MDIX	Yes All Ports
Others	DHCP, Multicast, Qos, IPV4/6

Hardware

Processore Type	Realtek
LED Panel	POE Activity / Data Activity

PD`S

IP Camera & IP Phone	Yes
----------------------	-----

General

Dimension	438*330*45mm
Weight	4.9kg
Storage Temp	-20°C ~ +60°C / 10% ~ 90% RH
Operation Temp	-15°C ~ +50°C / 10% ~ 90% RH
Power	90~220VAC - 2.9A
MTBF	100K hrs min. MIL-HDBK-217F (25°)
Rackmount	Support
Radiation	EN55016
Electromagnetic	